

FABRIC SEAL™ (N) FIRE RETARDANT LIQUID

THE ABSOLUTE BEST IN FIRE PROTECTION TECHNOLOGY™

[FABRIC SEAL CHOICES](#) | [TESTS](#) | [APPLICATION](#) | [MSDS](#) |

Total Solids:	12 % - 13 %
Weight per Gallon:	8.7 - 9.1 lbs
Specific Gravity:	1.05 - 1.10
pH:	5.5 - 7.0
Flash Point:	None
Color:	Water Clear
Coverage:	300 Square Feet - Gallon
Volatility:	Non-Volatile (Contains no VOC's)
Solvents:	Water (Contains no petroleum derivatives)
Toxicity:	Non-toxic - Not harmful to plants or animals.
Fungus Resistance:	Excellent
Mold Resistance:	Excellent
Bacteria Resistance:	Mildly resistant
Linear Shrinkage:	None
Moisture Absorption:	None
Corrosive:	Mildly, none when dry
Storage:	Temperature - 40-90°F, (4.44°C-32.22°C)
Shelf Life:	1 Year from Manufacturer Batch Date at proper temp.

(No PBDEs - Polybrominated diphenyl ethers)

RECOMMENDED USE:

Fabric Seal™ (N) Fire Retardant, INTERIOR, can be applied by spray or dipping applications. Spray at approximately 300 square feet per gallon by spray method or, if dipping materials, extract excess by use of spin cycle (washer), extractor (Industrial), or by wringing out (by hand). Then simply allow to air dry or force dry with a clothes dryer. This product may be used on: 100% natural fibers (i.e., cotton).

NOTE: FLAME SEAL RECOMMENDS RE-TREATMENT AFTER THREE (3) DRY CLEANINGS OR ONE MACHINE WASHING.

ENVIRONMENTAL REGULATIONS: This product *complies* with U.S. Federal Regulations concerning the use of lead in paint AND hydrocarbon emissions.

Rev-02-11-10

PRODUCTS ARE GUARANTEED TO PERFORM THEIR FIRE RETARDANT FUNCTION AS REPRESENTED BY THIRD PARTY TESTS, IF APPLIED ACCORDING TO MANUFACTURER'S PUBLISHED INSTRUCTIONS. PRODUCTS MAY NOT BE DILUTED OR ALTERED PRIOR TO USE.

There are no other warranties either expressed or implied since Flame Seal Products, Inc. cannot control the actual application of the products. Users must determine usability and suitability for their particular requirements, as well as compatibility with the exact materials to be treated or coated.

FLAME SEAL PRODUCTS, INC. 4025 Willowbend Blvd. # 310, Houston, Texas, 77025 USA, (713) 668 4291 office, (713) 668 1724 fax, www.flameseal.com
© Copyright of Flame Seal Products, Inc. All rights reserved, ® Registered Trademark of Flame Seal Products, Inc., TM Trademark of Flame Seal Products, Inc.